




Speed, Performance, Value - The Right Balance

- Supports remote scale of up to 4 load-cells for enhanced weighing and counting
- Up to 100 PLU's with description, unit weight and tare weight can be stored in memory
- RS-232 bi-directional interface
- Programmable for counting to a pre-set number of parts
- Memory accumulation of count
- Preset tare function
- Rechargeable battery with up to 70 hours operation / mains adapter supplied as standard
- Weighing
- Dual Counting facility
- Weight accumulation
- Parts counting
- Check counting
- Count accumulation



Technical Specifications

Model	CBD 3	CBD 6	CBD 15	CBD 30
Maximum capacity	3000g	6000g	15kg	30kg
Readability	0.1g	0.2g	0.5g	1g
Resolution	1:30000	1:30000	1:30000	1:30000
Tare range	-3kg	-6kg	-10kg	-30kg
Repeatability (S.D.)	0.1g	0.2g	0.5g	1g
Linearity (±)	0.2g	0.4g	1g	2g
Pan size	225x275mm			

General Specifications

Internal counting resolution	1:400,000
Tare functions	Full
Units of measurement	Kilogram (kg)
Applications	Counting Scale
Functions	Weighing, Parts Counting, Memory Accumulation Function, Preset Weight and Count with Alarm, up to 100 PLUs with description, unit & tare weight
Typical stabilisation time	2 Sec
Interface	Bi-directional RS-232 interface
Calibration	Automatic External
Display	3 x 6 digits LCD digital display
Power supply	9VDC, 800mA from external adapter
Operating temperature	0°C - 40°C
Other features	Accuracy enhancement for parts counting, internal rechargeable battery (up to 70 hours of operation)
Housing	ABS plastic, stainless steel platform
Overall dimensions (wxdxh)	315x355x110mm
Net weight	4.1kg

Key Accessories

- Adam Printer
- In-Use Cover pack of 10
- In-use Cover
- Range of Platforms for Remote Scale
- In-Use Cover pack of 5
- Thermal Paper Roll for Adam Printer
- RS-232 Cable
- AdamDU - Data Collection Program
- Hard Carry Case with Lock



Adam Equipment - offices worldwide

www.adamequipment.com